



TOLI Carpet Tile

YUTAKA 1000 <YU-1100>



YU1106

16 colorways available



YU1108

Technical Specifications

Product Description	Nylon Tufted Carpet Tile
Surface	BCF Nylon100%
Dye Method	Piece Dyed
Stain Protection	Stain Release (Antifouling Finished)
Base Fabric	Nonwoven Polyester
Backing	PVC and Glass Fiber
Size	500mm X 500mm X 6.0mm
Pile Height	3.0mm (level loop pile)
Gauge & Stitches	1/10 th gauge 14.5 stiches/inch
Packing & Net Weight	16pcs/box=4m ² /box (19.0kg/box)
Origin	Made in Japan

Performance Testing

Antistatic Property	Less than 1.0kv (JIS L 1021-16, at 23 degrees C, 25%RH)
Electrostatic Propensity	Maximum Average 1.1kv (AATCC 134)
Critical Radiant Flux	Class 2 Average CRF 0.22/cm ² or higher (ASTM E648)
Smoke Density	Less than 450 (ASTM E662)
Surface Flammability	Passes DOC FF 1-70 (ASTM D2859)
Flame-retardant Property	Fire Defense Law in Japan Authorized No. E2120129
Dimensional Stability	Less than 0.1% change (ASTM D7570)
Abrasion Resistance by Hexapod Tumble Drum Tester	Appearance Rating 4.0 / Color Change Rating 4.0 (ASTM D5252)
Tuft Bind	5.2 Lbs. (ASTM D1335)
Delamination Strength	Exceeds backing strength (ASTM D3936)
Colorfastness to Light	Rating 5.0 = No Change (AATCC 16)

Way of Installation



quarter turn

Environmental Certificate

CRI Green Label Plus	GLP9978
-----------------------------	---------

Product Notes

Specifications are subject to nominal manufacturing variances.
 Material supply and/or manufacturing processes may necessitate changes without notice.
 Colors may vary slightly from dye lot to dye lot.
 The use of chair pads under roller caster chairs may be required in order to maintain sufficient performance of the product.