TOLI Carpet Tile



NOCTURE <GX-8400>

NUCTURE \UA-04002		
	Technical Specifications	
	Product Description	Nylon Tufted Carpet Tile
	Surface	BCF Nylon100%
	Dyeing Method	Solution Dyed
	Stain Protection	Stain Release (Antifouling Finished)
	Base Fabric	Nonwoven Polyester
	Backing	PVC and Glass Fiber
	Size	500mm x 500mm x 8.5mm
GX8401	Pile Height	H6.0mm/L4.5mm (cut and loop pile)
4 colorways available	Gauge & Stitches	1/10 th gauge 12.0 stiches/inch
	Yarn Weight	29.5 oz/sq.yd
	Packing & Net Weight	16pcs/box=4m ² /box (20.2kg/box)
	Origin	Made in Japan
	Performance Testing	
	Antistatic Property	Less than 1.0kv (JIS L 1021-16, at 23 degrees C, 25%RH)
	Electrostatic Propensity	Maximum Average 1.8kv (AATCC 134)
	Critical Radiant Flux	Class 1 Average CRF 0.45/cm2 or higher (ASTM E648)
	Smoke Density	Less than 450 (ASTM E662)
	Surface Flammability	Passes DOC FF 1-70 (ASTM D2859)
	Flame-retardant Property	Fire Defense Law in Japan Authorized No. E2150032
	Dimensional Stability	Less than 0.1% change (ASTM D7570)
	Abrasion Resistance by Hexapod Tumble Drum Tester	Appearance Rating 3.0 / Color Change Rating 2.0 (ASTM D5252)
	Tuft Bind	11.6 Lbs. (ASTM D1335)
GX8403/TTN3109	Delamination Strength	4.2 Lbs/Inch (ASTM D3936)
	Colorfastness to Light	Rating 5.0 = No Change (AATCC 16)
	Way of Installation	
	t → → t quarter turn	monolithic
	Environmental Certificate	
	CRI Green Label Plus	GLP9977
	Product Notes	
	Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice. Colors may vary slightly from dye lot to dye lot. The use of chair pads under roller caster chairs may be required in order to maintain sufficientperformance of the product.	

TOLI Corporation - Global Department

2-10-4 Higashi-Shinbashi Minato-ku Tokyo 105-0021 Japan Phone: 813-5403-2078 Fax: 813-5472-6307