



TOLI Carpet Tile

YUTAKA2000 NATURE CRESCENDO <YU-2200> : ver. 2020



YU2225

6 standard colors and
2 custom colors available



YU2222/YU2226/YU2262



YU2222/YU2224

Technical Specifications

Product Description	Nylon Tufted Carpet Tile
Surface	BCF Nylon100%
Dyeing Method	Piece Dyed
Stain Protection	Stain Release (Antifouling Finished)
Base Fabric	Nonwoven Polyester
Backing	PVC and Glass Fiber
Size	500mm x 500mm x 7.3mm
Pile Height	H5.0mm / L3.5mm (textured loop pile)
Gauge & Stitches	1/10 th gauge 11.2 stitches/inch
Packing & Net Weight	16pcs/box=4m ² /box (21.0kg/box)
Origin	Made in Japan

Performance Testing

test item	test method	result
Electrostatic Propensity	AATCC 134	1.1 kv
Critical Radiant Flux	ASTM E648	Class 2 Average CRF 0.22/cm ² or higher
Smoke Density (flaming)	ASTM E662	Less than 450
Surface Flammability	ASTM D2859	Passes CPSC FF 1-70
Dimensional Stability	ASTM D7570	Less than 0.1% change
Abrasion	ASTM D5252	appearance 2.5 color change 2.0
Tuft Bind	ASTM D1335	9.0 Lbs.
Delamination Strength	ASTM D3936	Construction will not allow for a proper delamination.
Colorfastness to Light	AATCC 16	Rating 5.0 = No Change

Way of Installation



Quarter Turn



Monolithic

Environmental Certificate

CRI Green Label Plus	GLP9978
ISO14001 Registration	RE0707

Product Notes

Specifications are subject to nominal manufacturing variances.
Material supply and/or manufacturing processes may necessitate changes without notice.
Colors may vary slightly from dye lot to dye lot.
The use of chair pads under roller caster chairs may be required in order to maintain sufficient performance of the product.