



## TOLI Carpet Tile

# GA-400A



GA4934A

10 colorways available



### Technical Specifications

<b>Product Description</b>	Polypropylene Tufted Carpet Tile
<b>Surface</b>	Polypropylene 100%
<b>Dyeing Method</b>	Solution Dyed
<b>Base Fabric</b>	Nonwoven Polyester
<b>Backing</b>	PVC and Glass Fiber
<b>Size</b>	500mm x 500mm x 6.8mm
<b>Pile Height</b>	H 4.5mm / L 3.0mm (textured loop pile)
<b>Gauge &amp; Stitches</b>	1/10 <sup>th</sup> gauge 10.5 stiches/inch
<b>Yarn Weight</b>	13.3 oz/sq.yd
<b>Packing &amp; Net Weight</b>	20pcs/box=5m2/box (22.3 kg/box)
<b>Origin</b>	Made in Japan

### Performance Testing

<b>Antistatic Property</b>	Less than 1.0 kv (JIS L 1021-16, at 23 degrees C, 25%RH)
<b>Electrostatic Propensity</b>	Maximum Average 0.2 kv (AATCC 134)
<b>Smoke Density (flaming)</b>	Less than 450 (ASTM E662)
<b>Surface Flammability</b>	Passes DOC FF 1-70 (ASTM D2859)
<b>Flame-retardant Property</b>	Fire Defense Law in Japan Authorized No. E2190090
<b>Dimensional Stability</b>	Less than 0.1% change (ASTM D7570)
<b>Tuft Bind</b>	8.7 Lbs. (ASTM D1335)
<b>Delamination Strength</b>	Construction will not allow for delamination.
<b>Colorfastness to Light</b>	Rating 5.0 = No Change (AATCC 16)

### Way of Installation



quarter turn



monolithic

### Environmental Certificate

<b>CRI Green Label Plus</b>	N/A
-----------------------------	-----

### Product Notes

Specifications are subject to nominal manufacturing variances.  
 Material supply and/or manufacturing processes may necessitate changes without notice.  
 Colors may vary slightly from dye lot to dye lot.  
 The use of chair pads under roller caster chairs may be required in order to maintain sufficient performance of the product.

TOLI Corporation - Global Department  
 2-10-4 Higashi-Shinbashi Minato-ku Tokyo 105-0021 Japan  
 Phone: +81-3-5403-2078 Fax: +81-3-5472-6307