





TOLI Carpet Tile

GA-560



GA5602

Technical Specifications	
Product Description	Polypropylene Tufted Carpet Tile
Surface	Polypropylene 100%
Dyeing Method	Solution Dyed
Base Fabric	Nonwoven Polyester
Backing	PVC and Glass Fiber
Size	500mm x 500mm x 7.0mm
Pile Height	H 4.5mm / L 3.0mm (textured loop pile)
Gauge & Stitches	1/10 th gauge 13.0 stitches/inch
Yarn Weight	15.3 oz/sq.yd
Packing & Net Weight	20pcs/box=5m2/box (21.5kg/box)
Origin	Made in Japan
Performance Testing	
Antistatic Property	Less than 1.0 kv (JIS L 1021-16, at 23 degrees C, 25%RH)
Electrostatic Propensity	Maximum Average 0.1 kv (AATCC 134)
Smoke Density	Less than 450 (ASTM E662)
Surface Flammability	Passes DOC FF 1-70 (ASTM D2859)
Flame-retardant Property	Fire Defense Law in Japan Authorized No. E2150022
Dimensional Stability	Less than 0.1% change (ASTM D7570)
Abrasion Resistance by Hexapod Tumble Drum Tester	Appearance Rating 2.0 / Color Change Rating 2.5 (ASTM D5252)
Tuft Bind	7.9 Lbs. (ASTM D1335)
Delamination Strength	6.1 Lbs/Inch (ASTM D3936)
Colorfastness to Light	Rating 5.0 = No Change (AATCC 16)
Way of Installation	
 quarter turn	
Environmental Certificate	
CRI Green Label Plus	N/A
Product Notes	
Specifications are subject to nominal manufacturing variances. supply and/or manufacturing processes may necessitate changes without notice. vary slightly from dye lot to dye lot.	
Material Colors may The use of chair pads under roller caster chairs may be required in order to maintain sufficient performance of the product.	