



TOLI Carpet Tile

RC-1200



RC-1201

3 colorways available



RC-1204 / RC-1205

Technical Specifications

Product Description	Nylon Tufted Carpet Tile
Surface	BCF Nylon100%
Dyeing Method	Solution Dyed
Base Fabric	Woven Polyester and Polyester Fiber
Backing	PVC and Glass Fiber
Size	500mm x 500mm x 8.5mm
Pile Height	H5.5mm / M 4.5mm / L3.0mm (textured loop pile)
Gauge & Stitches	1/12 th gauge 11.5 stiches/inch
Yarn Weight	28.0 oz/sq.yd
Packing & Net Weight	16pcs/box=4m ² /box (22.8kg/box)
Origin	Made in Japan

Performance Testing

Antistatic Property	Less than 1.0kv (JIS L 1021-16, at 23 degrees C, 25%RH)
Electrostatic Propensity	Maximum Average 0.8kv (AATCC 134)
Surface Flammability	Passes DOC FF 1-70 (ASTM D2859)
Flame-retardant Property	Fire Defense Law in Japan Authorized No. E2160105
Dimensional Stability	Less than 0.1% change (ASTM D7570)
Abrasion Resistance by Hexapod Tumble Drum Tester	Appearance Rating 4.0 / Color Change Rating 4.0 (ASTM D5252)
Tuft Bind	7.5 Lbs. (ASTM D1335)
Colorfastness to Light	Rating 5.0 = No Change (AATCC 16)

Way of Installation



Environmental Certificate

CRI Green Label Plus	GLP9977
-----------------------------	---------

Product Notes

Specifications are subject to nominal manufacturing variances.
 Material supply and/or manufacturing processes may necessitate changes without notice.
 Colors may vary slightly from dye lot to dye lot.
 The use of chair pads under roller caster chairs may be required in order to maintain sufficient performance of the product.